

**Product Description:**

ATF TYPE F is a high friction automatic transmission fluid intended for use in automatic transmissions of all Ford vehicles that were built prior to 1977 and certain models built during 1977-1980 requiring fluids meeting Ford ESW-M2C33-F specification.

ATF TYPE F is formulated on high refined mineral base stock in combination with an unique additive package to reach the following properties.

- Extended thermal- and oxidation stability.
- Superior anti-wear technology protects transmission against wear.
- Improved low temperature fluidity provides fast circulation in cold climatic conditions.
- Compatible with all common seal materials.

ATF TYPE F exceeds the following performance criteria:

FORD M2C33-F
Borg-Warner

Ford M2C33-G

Ford M2C9007-AA



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m ³	ASTM D4052	867.2
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	38.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	172
Flash Point COC	°C	ASTM D92	195
Pour Point	°C	ASTM D7346	-48

Product Nr: 43170
Date Superseded: 16-12-2019

Date Issued: 31-12-2024
Revision nr: 03